

PACKAGE HIGHLIGHTS

- EPS
- 2500 (1131 kg) winch
- Handguard
- Mid-grade front bumper
- Rear hitch ball
- 12 in. aluminum wheels
- Changxing Clutch

ENGINE

Engine	550
Engine displacement	650
Type	46 hp / 50 N.m (37 lb-ft), single cylinder, DOHC, liquid cooled
Fuel delivery system	BOSCH EFI
Transmission	Changxing CVT L / H / N / R / P
Drive Train	Selectable 2WD/4WD with front differential lock
Driving Assistance	N/A

SUSPENSION

Front Suspension	Double A-arm 9.45 in. (240 mm) travel
Front Shocks	Twin oil shock absorbers
Rear Suspension	Double A-arm 9.84 in. (250 mm) travel
Rear Shocks	Twin oil shock absorbers

TIRES/WHEELS

Front Tires	25 x 8 x 12 in.
Rear Tires	25 x 10 x 12 in.
Wheels	12 in. Aluminum

BRAKES

Front	Dual 200 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 200 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS/CAPACITY

L x W x H	84.4 x 47.2 x 57.2 in. (2143 x 1200 x 1454 mm)
Wheelbase	51.9 in. (1320 mm)
Seat Height	37.4 in. (950 mm)
Ground Clearance	11 in. (280 mm)
Estimated Dry Weight*	882 lb (400 kg)
Towing Capacity	1786 lb (810 kg)
Front Rack Capacity	110 lb (50 kg)
Rear Tack Capacity	220 lb (100 kg)
Fuel Capacity	23 L
Battery	12V / 20Ah

FEATURES

Gauge	5 in. digital display
Power Steering	EPS
Lighting	LED headlights and taillights
Winch	2500 (1131 kg) winch
Protection	Mid-grade front and rear bumpers